

STANDARD FEATURES:

PAINTED, TEFC, 220/440/60 ELECTRIC MOTOR
HELICAL GEARBOX - 5:1 REDUCTION RATIO
350 RPM NOMINAL OUTPUT
ADJUSTABLE BRIDGE MOUNT
316SS WETTED PARTS
1" X 36" FMB SHAFT
SINGLE OR DUAL FOLDING IMPELLERS
WITH SET SCREW ATTACHMENT
ANALOG SPEED CONTROLLER (VFD)

OPTIONS:

32 Ra FINISH ON ALL WETTED PARTS
DIGITAL SPEED CONTROLLER (VFD)
FORK LIFT CHANNELS
TOTE CAP WITH VITON FLOATING SEAL

KNURLED KNOB
FOR EASY
LOCKDOWN

36" FMB

OPTIONAL SECOND
IMPELLER

BRIDGE MOUNT TOTE MIXERS MOUNT TO
CAGE STYLE TOTES UP TO 52" WIDE

OPTIONAL FORK
LIFT CHANNELS

VFD
(DIGITAL UPGRADE
SHOWN)

PLATE MOUNT
ADJUSTS FROM
END TO END

316 STAINLESS STEEL
SINGLE OR DUAL
FOLDING IMPELLERS

J HOOK HOLDDOWN BRACKET
ADJUSTS FROM END TO END

ELECTRIC MOTOR

HELICAL GEAR
REDUCER

316 STAINLESS STEEL
MIXER SHAFT

ANALOG VFD

DIGITAL VFD



DRAWN	JDF	DATE	6/10/13
CHECKED	PIC		6/10/13
PROPRIETARY AND CONFIDENTIAL			

THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF FUSION
FLUID EQUIPMENT LLC. ANY REPRODUCTION IN
PART OR AS A WHOLE WITHOUT THE WRITTEN
PERMISSION OF FUSION FLUID EQUIPMENT LLC IS
PROHIBITED.

WHILE FUSION FLUID EQUIPMENT LLC
STRIVES TO MAINTAIN THE INTEGRITY OF A
DESIGN AS APPROVED, FUSION FLUID
EQUIPMENT LLC RETAINS THE RIGHT TO MAKE
MODIFICATIONS DURING THE MANUFACTURING
PROCESS TO IMPROVE FIT, FORM, AND
FUNCTION OF THE DESIGN WITHOUT CUSTOMER
NOTIFICATION OR CONSENT.

FusionExpress
Mixing Equipment

TITLE: BRIDGE MOUNT TOTE MIXER
GEAR DRIVE ELECTRIC
WITH VFD

SIZE DWG. NO. REV
A SALES-BG-#T-#-V# A

SCALE: 1:16 WEIGHT: SHEET 1 OF 1

EST WT: 84-170 LBS (DEPENDING ON HP AND OPTIONS)